WWR2900

PEN BARCODE SCANNER



Big Business Tools. Small Business Attitude.

The WWR2900 pen barcode scanner is the perfect tool for repetitive data entry. Use the WWR2900 to scan barcodes on invoices, membership cards, and other barcoded material. The barcode data is instantly transferred to your open document, spreadsheet or database, helping your business save time and eliminate data entry errors.

The WWR2900 connects easily through your PC's USB port, and offers a compact, pen-style design that is ideal for desktop use.

WASP WWR2900 FEATURES

- Scans barcode data on contact
- Durable, ABS plastic construction provides reliability
- Can withstand multiple 6' drops to concrete
- Supports pre-amble and post-amble characters including function keys
- Reads linear (1D) barcodes including Code 39, Code 128 and UPC
- Compatible with optional stand for easy access and storage
- Includes 6' coiled USB cable

BENEFITS

- Easily scan barcodes on invoices, documents and membership cards by swiping the WWR2900 across the barcode
- Rapidly add data to your open application, eliminating data-entry errors and improving efficiency
- Ensure user comfort with the WWR2900's ergonomic, pen-style design
- Compact, space-saving design integrates easily into desktop workspaces
- Quickly install the WWR2900 through your PC's USB port without additional software or drivers

WASP WWR2900 COMMON USES

- Office
- Library
- Medical
- Marketing

WWR2900

PEN BARCODE SCANNER



Big Business Tools. Small Business Attitude.

SPECIFICATIONS

OPTICAL FEATURES	Depth of field: 1mm
	Resolution: 0.127mm (5 mil)
	Rate: 100mm - 600mm / Sec
	Tilt angle: 45 - 90 degree
ELECTRICAL CHARACTERISTICS	Light source: 650nm LED
	Sensor: Photo Diode
	Supply voltage: 5 VDC ± 10%
	Surge power: < 500mA
	Working current: 60mA ± 10mA
MECHANICAL CHARACTERISTICS	Dimensions: 150mm W x 29.6mm H x 22mm D
	Net weight: 76g
	Cable: 6' coiled USB
ENVIRONMENTAL CHARACTERISTICS	Operating temperature: 0˚C - 50˚C
	Storage temperature: -20˚C to 60˚C
	Relative humidity: 0% RH to 95% RH non-condensing
	Mechanical shock: 6.06ft (1.85) Drop onto concrete
	Safety certification: FCC class A and CE approval
1D (LINEAR) SYMBOLOGIES READ	Codabar, Code 3 of 9 (Code 39), Code 3 of 9 Full ASCII, Code 11, Code 32, Code 93, Code 128 (including UCC/EAN 128), EAN/JAN-8 (plus supplements), EAN/JAN-13 (plus supplements), Industrial 2 of 5 (25), Interleaved 2 of 5, ISBN, Matrix 25, MSI Plessey, UPC-A (plus supplements), UPC-E (plus supplements), China Post Code, RSS14, Telepen
PART NUMBERS	WWR2900 Pen Barcode Scanner with USB Cable: 633808142421
	WWR2900 Pen Barcode Scanner Stand: 633808142438